CURVE NO. 12-096 6-1-77	No. Stages	Eff. Change	MATERIAL	Eff. Change
	1	−1	IMP.—C.I.	−2
	2	0	IMP.—NI-RI	−1
	3		BOWL—BRZ.	−1
	4		BOWL—NI-R.	−1

15 DRHC — **1170** R.P.M.

SINGLE STAGE LAB PERFORMANCE WITH STANDARD MATERIALS. EFFICIENCY SHOWN FOR 2 OR MORE STAGES. HORSE POWER SHOWN FOR ONE STAGE BASED ON 2 STAGE EFFICIENCY. CORRECTIONS SHOULD BE MADE FOR STAGES AND MATERIAL.



EYE AREA — SQ. IN.	= 19.79		IMPELLER WT.-LBS.	= 25.6	
WR^2 PER IMPELLER	= 2.65	LB.-FT.^{2}	ONE STAGE WT.-LBS.	= 650	
MAX. SPHERE SIZE	= 0.625	in.	ADD'L STAGE WT.-LBS.	= 225	
MAX. NO. STD. STAGES	= 20		IMPELLER NUMBER	= 7DR17	
MAX. OPERATING P.S.I.	= 400		DISCH. SIZES	= 8,10,12	
STD. LATERAL	= 0.76	in.	SUCTION SIZES	= 10	
STD. SHAFT DIA.	= 1.937	in.	MAX. LATERAL	= 1.26	in.
MAX. SHAFT DIA.	= 2.187	in.	BOWL CONN.	FLANGED-COLLET	
MIN. SUBMERGENCE	= 15	in.	ADD 11	" PER ADDITIONAL STAGE.