

1770 RPM

ENCLOSED TYPE IMPELLER

13XKN

| NUMBER OF STAGES | EFFICIENCY CHANGE (NO. OF POINTS) |
|------------------|-----------------------------------|
| 1 | - 0 |
| 2 | - 0 |
| 3 | - 0 |

HORSEPOWER WILL BE AFFECTED BY CHANGE IN EFFICIENCY

PUMP DATA

| | |
|-------------------------|---------|
| Shaft Dia.(IN) | 1 15/16 |
| Maximum Sphere (IN) | 5/8 |
| Maximum Head (FT)* | 1733 |
| Min. Submergence (IN)** | 24 |
| Impeller Weight (LBS) | 23 |
| Thrust Constant (K) | 16.6 |
| Thrust Bal Const. (K) | N/A |
| Bowl O.D.(IN.) | 13 1/16 |
| Bowl Height (IN.) | 8 5/8 |
| Bell DIA. (T) (IN.) | 13 1/16 |
| Strainer height (IN.) | 10 3/4 |
| Impeller C-line(X)(IN.) | 6 3/4 |
| Eye Area (IN^ 2) | 33.7 |

NOTES

Performance indicated based on cold water with specific gravity of 1.0.

* Standard Construction.

** Minimum submergence over lip of bell to prevent vortexing.

Efficiency improvements are available in certain instances. Please contact the factory.

