

1760 RPM

ENCLOSED TYPE IMPELLER

6LKM

NUMBER OF STAGES EFFICIENCY CHANGE (NO. OF POINTS)

| | |
|---|-----|
| 1 | - 3 |
| 2 | - 2 |
| 3 | - 1 |

HORSEPOWER WILL BE AFFECTED BY CHANGE IN EFFICIENCY

PUMP DATA

| | |
|-----------------------------|---------|
| Shaft Dia. (IN) | 1 |
| Maximum Sphere (IN) | 3/16 |
| Maximum Head (FT)* | 1169 |
| Min. Submergence (IN)** | 8 |
| Impeller Weight (LBS) | 2.4 |
| Thrust Constant (K) | 2.1 |
| Thrust Bal Const. (K) | N/A |
| Bowl O.D. (IN.) | 5 5/8 |
| Bowl Height (IN.) | 4 3/4 |
| Bell DIA. (T) (IN.) | 5 13/16 |
| Strainer height (IN.) | 3 3/4 |
| Impeller C-line(X) (IN.) | 4 1/4 |
| Eye Area (IN ²) | 1.3 |

NOTES

Performance indicated based on cold water with specific gravity of 1.0.

* Standard Construction.

** Minimum submergence over lip of bell to prevent vortexing.

Efficiency improvements are available in certain instances. Please contact the factory.

PER STAGE PERFORMANCE

