


GOULDS PROPOSAL NO.	GOULDS S.O. NO.	INQUIRY NO.	CUSTOMER P.O. NO.	P.O. DATE	ITEM NO.	CUSTOMER	
PROJECT		SERVICE		GPM CAPACITY	FT. TDH	% EFFICIENCY	RPM



Curve No. E6414RMPC0	
Model 14RHMC	
RPM 1770	
EFFICIENCY CORRECTION	
1-STAGE	-1.0
2-STAGE	-0.5
3-STAGE	0.0
4-STAGE	0.0
Impeller ENCLOSED	
Ns = 3100	
K = 16.0 LBS/FT	
K(Bal.)= N/A	
Bowl O.D.	14.0"
Bowl Lateral	0.75"
Max. PSI	327
Disch size	10", 12"
GOULDS PUMPS	
TURBINE OPERATIONS Lubbock, Texas	
BOWL PERFORMANCE CURVE BASED ON PUMPING CLEAR, NON-AERATED WATER. RATED POINT ONLY IS GUARANTEED. CURVES REPRESENT SINGLE STAGE PERFORMANCE BASED ON TEST OF MULTI-STAGE BOWL ASSEMBLY. EFFICIENCY CORRECTION IS REQUIRED FOR LESSER STAGES.	