


GOULDS PROPOSAL NO.	GOULDS S.O. NO.	INQUIRY NO.	CUSTOMER P.O. NO.	P.O. DATE	ITEM NO.	CUSTOMER	
PROJECT	SERVICE			GPM CAPACITY	FT. TDH	% EFFICIENCY	RPM



Curve No.	
E6409WBPC1	
Model	9WALC
RPM	1770
EFFICIENCY CORRECTION	
1-STAGE	-2.0
2-STAGE	-1.0
3-STAGE	0.0
4-STAGE	0.0
Impeller	ENCLOSED
Ns =	1660
K =	3.75 LBS/FT
K(Bal.)=	N/A
Bowl O.D.	9.25"
Bowl Lateral	0.56"
Max. PSI	530
Disch size	5", 6", 8"
GOULDS PUMPS	
TURBINE OPERATIONS	
Lubbock, Texas	
BOWL PERFORMANCE CURVE BASED ON PUMPING CLEAR, NON-AERATED WATER. RATED POINT ONLY IS GUARANTEED. CURVES REPRESENT SINGLE STAGE PERFORMANCE BASED ON TEST OF MULTI-STAGE BOWL ASSEMBLY. EFFICIENCY CORRECTION IS REQUIRED FOR LESSER STAGES.	