BOWL T-83380



CHANGE EFFICIENCY AS FOLLOWS	NUM. OF POINTS	FOR NUMBER OF STAGES
LOWER	1	6
"	2	4
"	3	2
"	6	1

NOTE: ANY CHANGE IN EFFICIENCY AFFECTS EITHER THE HEAD OR HORSE POWER CORRESPONDINGLY.

HYDRAULIC PERFORMANCE

GUARANTEED AT THE DESIGNATED POINT ONLY AND IS CONTINGENT ON WELL PROPERLY FURNISHING PUMP WITH NON-AERATED OR NON-GASEOUS WATER FREE FROM ABRASIVES. PUMP BOWLS MUST BE PROPERLY ADJUSTED FOR THE HEAD AT WHICH THEY OPERATE AND MUST BE SUBMERGED

CURVE NO.	IMPELLER NO.	IMPELLER DIA.	TAKEN FROM
1	T-83411	5 23/32"	T-3886
2	T-83411	5 15/32"	T-3894
3	T-83411	5 7/32"	T-3895

PEERLESS PUMP DIVISION
FOOD MACHINERY CORPORATION
LOS ANGELES 31, CALIF.

PEERLESS PUMPS

PERFORMANCE PER STAGE
8" LA — DEEP WELL TURBINE PUMP
1760 — R. P. M.
SHEET NO. R-963

PRINTED IN U. S. A.



CHANGE EFFICIENCY AS FOLLOWS	NUMBER OF POINTS	FOR NUMBER OF STAGES
Lower	1	6
"	2	4
"	3	2
"	6	1

NOTE: ANY CHANGE IN EFFICIENCY AFFECTS EITHER THE HEAD OR HORSE POWER CORRESPONDINGLY

HYDRAULIC PERFORMANCE	CURVE NO.	IMPELLER NO.	IMPELLER DIA.	TAKEN FROM
GUARANTEED AT THE DESIGNATED POINT ONLY. Efficiency must be reduced for bronze & special material bowls - See Application Section	1	T83411	5-11/16	27933
	2	T83411	5-7/16	27935
	3	T83411	5-3/16	

PEERLESS PUMP DIVISION
FOOD MACHINERY AND CHEMICAL CORPORATION
LOS ANGELES 31, CALIFORNIA

PEERLESS PUMPS

PERFORMANCE PER STAGE

8 LA

1760 R. P. M.

SHEET NO. 2812915r