


MODEL: 70 J4

SIZE: 4"

RPM: 3450

HP: 5

CURVE NO: ST1003




STARITE INDUSTRIES, INC.

Water Equipment Division

293 SOUTH WRIGHT STREET / DELAVAN, WISCONSIN 53115 / U.S.A.

DATE: APRIL 19, 1979

TOTAL HEAD/FEET



CAPACITY US GPM

DEEP WELL SUBMERSIBLE TURBINE

CURVE No. ST1003

IMPELLER DATA

IMPELLER No. P5-33P
TYPE Enclosed - Plastic
DIAMETER 2.838 x 41°
EFFECTIVE EYE AREA 2.27 Sq. Inches
NUMBER OF VANES 7
THRUST CONSTANT K _____ Lbs./Ft. of Head
WR² _____ Lbs. Ft.²
WEIGHT 0.11 Lbs.
EYE FLUID VELOCITY 0.141 Ft./Sec./G.P.M.
PERIPHERAL VELOCITY 15.05 Ft./Sec./Inch of Impeller Dia.


BOWL ASSEMBLY DATA

BOWL No. P101-51 (C.I.)
CONNECTION TYPE Screwed
DISCHARGE TAPPING 2-1/2" NPT
PUMP SHAFT DIA. 1/2"
NUMBER OF STAGES 12

PERFORMANCE DATA

PERFORMANCE CURVE BASED ON 4 " MOTOR
 WITH SPEED OF 3460 RPM AT BEP. USE OF
 DIFFERENT SIZE MOTOR, OR DIFFERENT SPEED
 CHARACTERISTIC WILL CHANGE PERFORMANCE.

DIMENSIONS



- A-OVERALL LIQUID END LENGTH
- B-SUCTION CONNECTION LENGTH
- C-STAGE LENGTH
- D-DISCHARGE CONNECTION LENGTH
- E-BOWL DIAMETER
- F-DIAMETER ACROSS LEAD GUARD
- G-MOTOR DIAMETER
- H-MOTOR LENGTH
- J-OVERALL PUMP LENGTH-INCLUDING MOTOR

DIMENSION	A	B	C	D	E	F	G	H	J
INCHES	48-15/16	4-11/16	3-5/16	4-7/8	3-9/16	3-13/16	3-11/16	36-1/16	85

UNIT WEIGHTS - POUNDS

MOTOR SIZE	4"	
PUMP INCLUDING MOTOR	113	
LIQUID END ONLY	47.5	