


MODEL: 800PI0

SIZE: 10"

RPM: 3450

HP: 25

CURVE NO: ST 1097




STAR-RITE INDUSTRIES, INC.

Water Equipment Division

293 SOUTH WRIGHT STREET, DELAVAN, WISCONSIN 53115 U.S.A.

DATE: JULY 19, 1979

TOTAL HEAD FEET



CAPACITY U.S. G.P.M.

DEEP WELL SUBMERSIBLE TURBINE

CURVE No. ST1097

IMPELLER DATA

IMPELLER No. P5-40DB
 TYPE Enclosed - Brass
 DIAMETER 6.200 x 26°
 EFFECTIVE EYE AREA 11.18 Sq. Inches
 NUMBER OF VANES 5
 THRUST CONSTANT K 5.36 Lbs./Ft. of Head
 WR² _____ Lbs. Ft.²
 WEIGHT 9.5 Lbs.
 EYE FLUID VELOCITY .029 Ft./Sec./G.P.M.
 PERIPHERAL VELOCITY 15.05 Ft./Sec./Inch of Impeller Dia.


BOWL ASSEMBLY DATA

BOWL No. P101-62E (C.I. Enameled)
 CONNECTION TYPE Bolted
 DISCHARGE TAPPING 8" NPT
 PUMP SHAFT DIA. 1-1/2"
 NUMBER OF STAGES 1

PERFORMANCE DATA

PERFORMANCE CURVE BASED ON 6 " MOTOR
 WITH SPEED OF 3430 RPM AT BEP. USE OF
 DIFFERENT SIZE MOTOR, OR DIFFERENT SPEED
 CHARACTERISTIC WILL CHANGE PERFORMANCE.

DIMENSIONS



- A-OVERALL LIQUID END LENGTH
- B-SUCTION CONNECTION LENGTH
- C-STAGE LENGTH
- D-DISCHARGE CONNECTION LENGTH
- E-BOWL DIAMETER
- F-DIAMETER ACROSS LEAD GUARD
- G-MOTOR DIAMETER
- H-MOTOR LENGTH
- J-OVERALL PUMP LENGTH-INCLUDING MOTOR

DIMENSION	A	B	C	D	E	F	G	H	J
INCHES	32-3/4	15-7/8	8-1/4	8-19/32	9-5/8	10-3/16	5-1/2	38-3/16	70-15/16

UNIT WEIGHTS - POUNDS

MOTOR SIZE	6"	
PUMP INCLUDING MOTOR	359	
LIQUID END ONLY	178	