


MODEL: 950P8

SIZE: 8"

RPM: 3450

HP: 25

CURVE NO: ST1069




STAR-RITE INDUSTRIES, INC.

Water Equipment Division

293 SOUTH WRIGHT STREET / DELAVAN, WISCONSIN 53115 / U.S.A.

DATE: FEB. 9, 1979

TOTAL HEAD / FEET



CAPACITY U.S. G.P.M.

# DEEP WELL SUBMERSIBLE TURBINE

CURVE No. ST1069

## IMPELLER DATA

IMPELLER No. P5-35DA  
 TYPE Enclosed - Brass  
 DIAMETER 5.190 x 26°  
 EFFECTIVE EYE AREA 12.14 Sq. Inches  
 NUMBER OF VANES 7  
 THRUST CONSTANT K 4.65 Lbs./Ft. of Head  
 WR<sup>2</sup> \_\_\_\_\_ Lbs. Ft.<sup>2</sup>  
 WEIGHT 4.4 Lbs.  
 EYE FLUID VELOCITY 0.026 Ft./Sec./G.P.M.  
 PERIPHERAL VELOCITY 15.05 Ft./Sec./Inch of Impeller Dia.


## BOWL ASSEMBLY DATA

BOWL No. P101-50 (C.I.)  
 CONNECTION TYPE Screwed  
 DISCHARGE TAPPING 6" NPT  
 PUMP SHAFT DIA. 1-1/4"  
 NUMBER OF STAGES 1

## PERFORMANCE DATA

PERFORMANCE CURVE BASED ON 6 " MOTOR  
 WITH SPEED OF 3440 RPM AT B.E.P. USE OF  
 DIFFERENT SIZE MOTOR, OR DIFFERENT SPEED  
 CHARACTERISTIC WILL CHANGE PERFORMANCE.

## DIMENSIONS



- A-OVERALL LIQUID END LENGTH
- B-SUCTION CONNECTION LENGTH
- C-STAGE LENGTH
- D-DISCHARGE CONNECTION LENGTH
- E-BOWL DIAMETER
- F-DIAMETER ACROSS LEAD GUARD
- G-MOTOR DIAMETER
- H-MOTOR LENGTH
- J-OVERALL PUMP LENGTH-INCLUDING MOTOR

DIMENSION	A	B	C	D	E	F	G	H	J
INCHES	28-1/4	13-3/8	6-3/4	8-1/8	7-3/8	7-15/16	5-1/2	38-3/16	66-7/16

### UNIT WEIGHTS - POUNDS

MOTOR SIZE	6"	
PUMP INCLUDING MOTOR	288.5	
LIQUID END ONLY	107.5	